BOSTOOLS.NL
Kleiland 11
8271RV IJsselmuiden NL
+31383332508
info@bostools.nl

EPS150TDE-3A

Geluidsgedempte stroomaggregaten met Volvo watergekoelde dieselmotor, 1500tpm, 50Hz, 4-takt



Aggregaat

kVA maximaal	165
kVA continu	150
kVA	50kVA @ 1~230V 150kVA @ 3~400V
Ampère (continu)	217A @ 1~230V 217A @ 3~400V
Afmetingen (lxbxh)	330x122x197 cm
Gewicht	2388 kg
Gewicht incl. olie, excl. brandstof*	2245 kg

**plus koelvloeistof indien watergekoeld*

Motor

Merk / Type	Volvo TAD751GE
PK maximaal	197
Vermogen	145kW max., diesel, watergekoeld
Toeren per minuut	1500
Cilinder	6
Cilinderinhoud	7150 cm^3
Verbruik @75% last	28 liter/uur
Tank	288 liter
Autonomie @75%	10,3 uur
Geluidsniveau	72 dB(A) @7 m = LWA 97
Batterij spanning	24V

Alternator

Merk / Type	Leroy Somer LSA44.3L10 AREP - borstelloos
Nominale spanning	3~400V en 1~230V
Frequentie	50Hz
Beschermingsgraad	Leroy Somer system 4
Controller	Deep Sea 4520

Kleiland 11
8271RV IJsselmuiden NL
+31383332508
info@bostools.nl

EPS150TDE-3A

Versie

- 1 socket 230V - 16A + 1 socket CEE 230V - 32A + 1 socket CEE 400V - 32A 5 p. + 1 socket CEE 400V - 125A 5 p.
- 3 Amperemeters
- Alternator Regulation Excitation Polymorphic
- Automatic voltage regulator
- Bunded fuel tank
- Deep Sea Electronics module DSE4520 up to 275kVA and DSE7420 as of 300kVA
- Double low fuel level switch (alarm + shut down)
- Earth leakage protection 30mA-30A, adjustable, with earth pin and 4m earth-cable
- Electric start, maintenance free battery included
- Emergency stop
- Frequency meter
- Fuel level meter
- High temperature security
- Hour counter
- Low coolant level switch
- Low oil pressure guard
- Magneto-Stop
- Manual fuel feed pump
- Oil drain pump
- Securing eyes for transportation
- Terminal power connection
- Thermal magnetic breaker with tripping coil and with individual thermal magnetic breakers on each socket
- Voltmeter
- Water separator / Fuel prefilter